




STONETECH® Honing Powder

STONETECH® Honing Powder offer extra fine to coarse grits that create even honed finishes.

**Globally Proven
Construction Solutions**



FEATURES/BENEFITS

- Creates an even, honed, flat finish
- Prepares stone for polishing and shining
- Different grits eliminate mild to deep scratches
- Non-acidic
- Available in 180, 280, 400, 600, and 800 grit levels
- Designed for professional use

USES

- Countertops
- Backsplashes
- Floors
- Walls

DISTRIBUTOR

Sareen Stone Pty Ltd
Unit 8, 43 Herbert Street
Artarmon NSW 2064 Australia

Telephone: 02 9666 9222
Website: www.sareenstone.com.au

RECOMMENDED SURFACES

Natural stone, such as most:

- Marble
- Limestone
- Travertine
- Terrazzo

PACKAGING

850g:

- 180 Grit, 6 units per case
- 280 Grit, 6 units per case
- 400 Grit, 6 units per case
- 600 Grit, 6 units per case
- 800 Grit, 6 units per case

Approximate Coverage

Depending on stone type, texture and porosity; the site conditions, and the methods of use, the following rates of coverage will vary.

Up to 408 m²/kg – 400 Grit/180 Grit

Up to 309.7 m²/kg – 280 Grit/600/800 Grit

Storage and Handling Instructions

CAUTION: MAY CAUSE MILD EYE AND RESPIRATORY IRRITATION. Do not ingest. Avoid contact with eyes and skin. Avoid inhalation of dust. KEEP OUT OF THE REACH OF CHILDREN

Cautions

- Consult SDS for more safety information.
- Inhalation: Remove victim to fresh air. Get medical attention if symptoms persist.
- Skin contact: Wash area with soap and water. Get medical attention if irritation develops or persists.
- Eye contact: Do not rub eyes. Flush eyes thoroughly with water for at least 15 minutes. Get medical attention if irritation develops or persists.
- Ingestion: Rinse mouth and drink plenty of water. Only induce vomiting at the instruction of medical personnel. Get medical attention if any discomfort occurs

TECHNICAL DATA

Physical Properties

Form	Powder
Colour	White
Odour	None
Specific Gravity	3.6

INSTALLATION

Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine ease of application and desired results. Allow new grout installations to cure for a minimum of 72 hours prior to application. Make sure surface is clean, dry and free of waxes and coatings.

Directions

If surface is heavily soiled, pre-clean with STONETECH® KlenzAll™ Cleaner if needed.

1. Mask off and protect any baseboards or adjacent areas to avoid splashing and overspray onto surfaces not intended to be treated.
2. If you are using a variety of abrasive grits, ensure that the surface is well rinsed and a new pad is used for each changeover.
3. Apply approximately 1/2 cup (114 g) STONETECH Honing Powder plus 1 cup (230mL) clean water directly onto the stone surface.

4. Refinish using a hand orbital sander or weighted floor machine at 59-64 kg. 175 rpm, fitted with a natural hair pad.
5. Keep compound wet while refinishing with plenty of water. Add STONETECH Honing Powder as needed.
6. Refinish area until the desired level of hone has been achieved.
7. Rinse well and use a wet vacuum or hot water extraction unit to remove all remaining compound.
8. Clean equipment with water. Use successively higher numbered grits of STONETECH Honing Powder to close the face of the stone and follow with STONETECH Polishing Powder as applicable.

AVAILABILITY AND COST

Availability

LATICRETE® and STONETECH and LATAPOXY® materials are available worldwide.

For Distributor information:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

For online distributor information, visit LATICRETE at www.laticrete.com.au

Cost

Contact a LATICRETE Distributor in your area.

MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the Sealer, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH Stone & Tile Cleaner is recommended. For tough or difficult to remove soil use STONETECH KlenzAll™ Cleaner, a nylon scrubbing pad or a long handled stiff bristle brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 1262 Stone and Tile Care Guide.

TECHNICAL SERVICES

Technical assistance

Information is available by calling:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

Fax: 07 3865 2250

Technical and safety literature

To acquire technical and safety literature, please visit our website at www.laticrete.com.au

DISCLAIMER

- The information contained in this document is given in good faith and to the best of our knowledge is true and accurate.
- This information is subject to change without notice and it is the responsibility of the user to obtain up to date and current information.
- The use of this product is beyond our control and LATICRETE® is not responsible for any loss or damage arising from the incorrect use of this product.
- Efflorescence is a normal condition of Portland cement and is not covered by any warranty.

LATICRETE Australia Pty Ltd
29 Telford Street, Virginia
QLD 4014 Australia
1800 331 012
www.laticrete.com.au