



STONETECH® Oil Stain Remover

STONETECH® Oil Stain Remover is designed to remove oil-based stains without discolouring the surface of natural stone.

**Globally Proven
Construction Solutions**



FEATURES/BENEFITS

- Pulls out deep-set oil stains
- Leaves no permanent residue
- Easy to use
- Will not discolour stone

USES

(Interior and Exterior)

- Countertops
- Floors

DISTRIBUTOR

Sareen Stone Pty Ltd
Unit 8, 43 Herbert Street
Artarmon NSW 2064 Australia

Telephone: 02 9666 9222

Website: www.sareenstone.com.au

RECOMMENDED SURFACES

Natural stone, masonry and cementitious grout such as:

- Marble
- Granite
- Limestone
- Travertine
- Slate
- Sandstone
- Concrete
- Quartzite

PACKAGING

- 88.7mL Can, 6 units per Case, 300 units per Pallet
- 473mL, 6 units per Case, 300 units per Pallets

Approximate Coverage

- 517 – 1034 cm² of surface at 6mm thickness per 473ml.
- 97-194 cm² of surface at 6mm thickness per 88.7ml can.

VOC content:

Not Regulated

Cautions

Consult SDS for more safety information.

- Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
- Skin contact: Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin rash or an allergic skin reaction develops, get medical attention.
- Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
- Ingestion: Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention if any discomfort continues.

Storage and Handling Instructions

COMBUSTIBLE. HARMFUL IF SWALLOWED. Do not ingest. Avoid prolonged exposure to vapours. Use only in a well-ventilated area. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. Avoid contact with eyes and skin. Wear solvent resistant gloves such as nitrile gloves. KEEP OUT OF THE REACH OF CHILDREN. Do not store above 38 °C. Do not mix with other chemicals. Do not release to natural waterways.

TECHNICAL DATA

Physical Properties

Form	Paste
Colour	Grey
Odour	Lemon

INSTALLATION

Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine that the desired results will be achieved. Make sure surface is clean, dry, and free of waxes and coatings. Ensure that area is well-ventilated and keep children and pets away from the area during application and until surface is clean and dry.

Directions

1. Using a plastic or wood spatula, stir thoroughly to mix the paste.
2. Apply a 6mm thick layer of paste to the stain. Ensure that the paste extends at least 25- 50mm beyond the edge of the stain.
3. Do not cover.
4. Allow 48–72 hours for paste to completely dry.
5. Using a plastic spatula, remove dried product and discard.
6. Allow solvent to completely dry from the stone.
7. If stain is not completely gone after drying, repeat process.
8. Clean up residue and tools with mineral spirits.
9. Once the surface is dry, reseal the cleaned area with a STONETECH® Sealer (e.g. STONETECH BulletProof®).

AVAILABILITY AND COST

Availability

LATICRETE® and STONETECH and LATAPOXY® materials are available worldwide.

For Distributor information:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

For online distributor information, visit LATICRETE at www.laticrete.com.au

Cost

Contact a LATICRETE Distributor in your area.

MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the Sealer, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH Stone & Tile Cleaner is recommended. For tough or difficult to remove soil use STONETECH KlenzAll™ Cleaner, a nylon scrubbing pad or a long handled stiff bristle brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 1262 Stone and Tile Care Guide.

TECHNICAL SERVICES

Technical assistance

Information is available by calling:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

Fax: 07 3865 2250

Technical and safety literature

To acquire technical and safety literature, please visit our website at www.laticrete.com.au

DISCLAIMER

- The information contained in this document is given in good faith and to the best of our knowledge is true and accurate.
- This information is subject to change without notice and it is the responsibility of the user to obtain up to date and current information.
- The use of this product is beyond our control and LATICRETE® is not responsible for any loss or damage arising from the incorrect use of this product.
- Efflorescence is a normal condition of Portland cement and is not covered by any warranty.

LATICRETE Australia Pty Ltd
29 Telford Street, Virginia
QLD 4014 Australia
1800 331 012
www.laticrete.com.au